# ISOFAN<sup>e</sup> FOLLOW THE EVOLUTION!





ISOFAN enamel with an **innovative formulation (DBTL-free)**, improved **speed of drying even at room temperature** and easy to use with most popular application systems. As it is an **integral part of the Lechsys system**, its portability all over the world is guaranteed.

Accompanied by a rationalised portfolio of hardeners and thinners, it is completed with a major expansion of tinters to allow access to a wider range of colours: this not only ensures an alignment with sector-specific systems of commercial vehicles, but it also extends its application to other sectors where required



**ISOFAN**<sup>e</sup> FOLLOWTHE EVOLUTION!





to other sectors, where high quality and aesthetics standards are



SILVER GUARD, a sanitising additive with silver ions, can be added to the product.



Along with a very high gloss film, high chemical and mechanical resistance and easy polishing, ISOFAN also presents new chromatic proposals to match the most recent and widespread colours.



## BINDER ISOFAN NEUTRAL 44501

in the ratio **75/25 binder/tinters** by volume and in the L3.75 pre-dosed can, it is proposed to obtain the most popular colours in the **commercial vehicle sector and in the general industry**. In the ratio 60/40 binder/tinters and in the L3.0 pre-dosed can using the new six tinters with higher opacity, it is indicated for the more critical colours in the area of yellows, reds and oranges.

## BINDER ISOFAN WHITE 44500

in the ratio **95/5 binder/tinters by** volume and in the L3.80 pre-dosed can it has been conceived to improve the opacity in the area of whites and derived colours.

#### 6 NEW TINTERS WITH HIGHER CONCENTRATION

are included in the range to produce colours that have a more critical opacity, in the area of yellows, reds and oranges.

LN29508 TB LECHSYS SUNSHINE YELLOW LN29515 TB LECHSYS WARM YELLOW LN29518 TB LECHSYS HYPER YELLOW LN29522 TB LECHSYS WARM ORANGE LN29524 TB LECHSYS ORANGE LN29548 TB LECHSYS SCARLET RED

### **3 NEW DEDICATED HARDENERS**

in the version 13600 ISOFAN HARDENER 13500 ISOFAN HARDENER FAST 13700 ISOFAN HARDENER ULTRA FAST

### 2 NEW THINNERS

formulated with the same logic, 00550 ISOFAN THINNER and 00560 ISOFAN THINNER SLOW.



STANDARD GLOSSY



ISOFAN





## MODULAR PROPOSAL IN THREE DIFFERENT CONFIGURATIONS



## BASIC CONFIGURATION ISOFAN NEUTRAL BINDER

ISOFAN NEUTRAL binder is **inserted into the Lechsys tinting system** to obtain all the colours proposed in the Lechler Master Chroma Advanced, Master Industry collections and in the most popular colour fans (RAL, NCS, British Standard).



Basic configuration integrated by a white binder which is inserted into the Lechsys Tinting System and allows a colour proposal enhanced by more specific **solutions for the most important colour and opacity needs** in the area of whites and derived colours.



## PREMIUM CONFIGURATION ISOFAN NEUTRAL, ISOFAN WHITE BINDER

The Elite configuration can be further extended in the Premium configuration with the **6 new higher concentrated tinters** for the highest aesthetic and opacity standards also in the range of more critical colours (**yellow, orange and red**). In support of that configuration an integration of the Master Chroma Advanced collection has been envisaged with **two new available colour fans**, for a total of about **200 new colours**.











COMMERCIAL VEHICLES

FITTING OF SPECIAL VEHICLES



COLD STORES

AGRICULTURAL, BUILDING & EARTH-MOVING MACHINES

MEANS OF URBAN TRANSPORT (BUSES, TRAMWAYS, UNDERGROUNDS AND MONORAILS)

SPECIAL MEANS OF TRANSPORT (CABLE CARS AND FUNICULARS)

SPORT EQUIPMENT

URBAN & SUBURBAN FURNITURE

MEDICAL AND AESTHETIC FOUIPMENT

HABITAT INTERIOR



HIGHLIGHTS It was developed utilising a technology with low environmental impact (VOC < 420 g/l) to be compliant with the directive 2004/42/CEE It's **DBTL-free** to be an even more a state-of-the-art product as concerns safety The innovative formulation allows for extremely fast drying at room temperature and a **dust-free** time up to just 20 minutes after the application Great hardness of the **paint film** and **surface slipperiness** Product **aesthetical aspect of the highest quality**, endowed with high **covering power**, brilliance and Excellent colour matching reliability at every level High light and weather resistance, proved through strict durability tests This enamel is easy to apply both with traditional spray gun, HVLP and Airmix, to achieve an excellent flow and a good vertical hold Quality and safety of the painting processes both in dry-on-dry and wet-on-wet process It generates painting processes compliant with **medium/high corrosion** classes of ISO 12944 with the most used primers from the Lechsys Systems









Color Design



Isofan, as for its aesthetic quality, is a perfect solution for the colour reproduction of the Color Design collections, such as Colors for a new life and Color Trend Consultant Classics.

#### Master Chroma Advanced

is the exclusive colour collection consisting of over 2.800 solid colour references, extended by two other new colour fans (L0990216N1 Master Chroma Advanced Updating 2021)

#### Master Industry

is the colour collection of ca. 1.100 colours containing the most popular solid and metallic colours spread on the market by the main manufacturers of Industrial Vehicles, recently supplemented by over 200 new pastel and metallic colour chips that are most popular on the market (L0990869N1 Master Industry Update I-2020).

#### Map Cross Reference

is an important tool for a precise cross reference of the colour proposals from these colour collections with the colours of the different Truck Manufacturers.



#### Color Reader

is an "ultra-portable" reader for direct measurement of solid colours on the surface and an immediate matching with the thousands of colours present in the Industry Master Chroma Advanced, Master Industry, RAL and NCS collections.

#### The Spectrophotometer

The fixed or portable spectrophotometer allows the preparation or formulation of solid colours according to the sample.



## EQUIPMENT TO SUPPORT THE OPERATOR IN AN INTUITIVE AND EFFICIENT WAY

#### The Lechsys tinting machine

is the mixing device. All dispensers of the tinters are equipped with stirring lids for quick and efficient mixing.

#### The Work Station

is combined with it and provides the ideal support to organise all tools necessary for colour reproduction and control.

#### Lechler MAP

guides the operator in the search for formulations, including customised formulations and in many other functions.

## AT THE CUSTOMER'S SERVICE

### Centre for Excellence

intended for training and professional odating with candidates attending the CFE r through dedicated online courses and a rompt technical and instrumental assistane both in the field and by phone.

#### The website www.lechler.eu

lows you to access to information on roducts, courses and industry news, as ell as technical and safety documentation, vailable for download.



LECHLER S.P.A. 22100 Como - Italia Via Cecilio, 17 Tel. +39.031 586 111 Fax +39.031 586 206 info@lechler.eu

LECHLER COATINGS LTD. Unit 42, Pochin Way - Middlewich Cheshire CW10 0GY - UK Tel. +44 (0) 1606 738.600 Fax +44 (0) 1606 738.517 lechler.uk@lechler.eu

LECHLER COATINGS FRANCE S.A.R.L.

Parc d'activité Actipole 296, rue de la Béalière F-38113 Veurey-Voroize - France Tel. +33(0) 4 76.53.71.81 Fax +33(0) 4 76.53.71.89 lechler.france@lechler.eu

LECHLER COATINGS IBERICA, S.L.

Calle Primer de Maig, 25-27 08908 L'Hospitalet de Llobregat Barcelona - España Tel. +34 93.264.93.20 Fax +34 93.264.93.21 lechler.iberica@lechler.eu

LECHLER COATINGS GMBH

Lilienthalstraße 3 (Halle 12) D-34123 Kassel - Deutschland Tel. +49 (0) 561 988.380 Fax +49 (0) 561 988.38.38 lechler.de@lechler.eu

#### LECHLER DO BRASIL S.A.

Rua 2, Distrito Industrial IV n. 10 Bairro: São Lucas CEP: 95360-000 Paraí (Rio Grande do Sul) - Brasil Tel/Fax: +55 54 3477 1882/2107 lechlerdobrasil@lechler.com.br

www.lechler.eu





UNI EN ISO 9001:2015 UNI EN ISO 14001:2015



